

**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
 Acetoxy Sanitary Sealant**
1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: GES Waterford Plant
 260 Hudson River Rd
 Waterford NY 12188
Revised: 06/22/2005
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: Mixture

HMIS

Flammability: 1 Reactivity: 0 Health: 0 Prot. Equipm.:

NFPA

Flammability: 1 Reactivity: 0 Health: 1 Special Haz.:

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Methyltriacetoxysilane	4253-34-3	5 - 10 %
Octamethylcyclotetrasiloxane	556-67-2	5 - 10 %
<u>B. NON-HAZARDOUS</u>		
Siloxanes & Silicones, Dimethylpolymers w/Methylsilsesquioxanes	68554-67-6	10 - 30 %
Treated Filler	68611-44-9	10 - 30 %
Dimethylpolysiloxane	70131-67-8	60 - 90 %

3. HAZARDS IDENTIFICATION
EMERGENCY OVERVIEW

WARNING! May be harmful if swallowed. Irritating to eyes, respiratory system and skin. Adverse liver and reproductive effects reported in animals.

Form: solid Color: white Odor: Acetic acid



**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
Acetoxy Sanitary Sealant**

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed.

SKIN

Uncured product contact will irritate lips, gums and tongue. Skin irritation is possible after contact with the uncured product.

INHALATION

Inhalation of vapors may cause irritation of the respiratory tract. Applies in uncured state.

EYES

Eye irritation is possible after contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

Liver; Reproductive hazard.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

dermal

OTHER

Acetic acid released during curing. This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 F (150 C) and above in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. An MSDS for formaldehyde is available from GE Advanced Materials - Silicones.

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. Get medical attention if irritation persists.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.



**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
Acetoxy Sanitary Sealant**

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT:

METHOD:

not applicable

IGNITION TEMPERATURE:

Unknown

FLAMMABLE LIMITS IN AIR - LOWER (%):

not applicable

FLAMMABLE LIMITS IN AIR - UPPER (%):

not applicable

SENSITIVITY TO MECHANICAL IMPACT:

No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

STORAGE

Store away from heat, sources of ignition, and incompatibles. Keep out of the reach of children. Keep container tightly closed.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Product releases acetic acid during application and curing. Use only in well-ventilated areas. Avoid contact with skin and eyes. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation.

**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
 Acetoxy Sanitary Sealant**
8. EXPOSURE CONTROLS / PERSONAL PROTECTION
ENGINEERING CONTROLS

Eyewash stations; Showers; Exhaust ventilation

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29 CFR 1910.134).

PROTECTIVE GLOVES

Impermeable or chemical resistant gloves.

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	not applicable
VAPOR PRESSURE (20 C) (MM HG):	Unknown
VAPOR DENSITY (AIR=1):	
FREEZING POINT:	not applicable
MELTING POINT:	not applicable
PHYSICAL STATE:	solid
ODOR:	Acetic acid
COLOR:	white
EVAPORATION RATE (BUTYL ACETATE=1):	
SPECIFIC GRAVITY (WATER=1):	1.05
DENSITY (KG/M3):	1,050.00 KG/M3
ACID / ALKALINITY (MEQ/G):	Unknown
pH:	not applicable
VOLATILE ORGANIC CONTENT (VOL):	not applicable

**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
Acetoxy Sanitary Sealant**

SOLUBILITY IN WATER (20 C):	insoluble
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Soluble in toluene
VOC EXCL. H2O & EXEMPTS (G/L):	20.00

10. STABILITY AND REACTIVITY**STABILITY**

Stable

HAZARDOUS POLYMERIZATION

Will not occur

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTScarbon dioxide (CO₂); Carbon monoxide; Acetic acid; Silicon dioxide.; formaldehyde**INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION**ACUTE ORAL**

Unknown

ACUTE DERMAL

Unknown

ACUTE INHALATION

NONE FOUND

OTHER

Octamethylcyclotetrasiloxane Ingestion: Rodents given large doses via oral gavage of octamethylcyclotetrasiloxane (1600 mg/kg day, 14 days) developed increased liver weights relative to unexposed control animals due to hepatocellular hyperplasia (increased number of liver cells which appear normal) as well as hypertrophy (increased cell size). Inhalation: In inhalation studies, laboratory rodents exposed to octamethylcyclotetrasiloxane (300 ppm five days week, 90 days) developed increased liver weights in female animals relative to unexposed control animals. When the exposure was stopped, liver weights returned to normal. Microscopic examination of the liver cells did not show any evidence of pathology. Inhalation studies utilizing laboratory rabbits and guinea pigs showed no effects on liver weights. Inhalation exposures typical of industrial usage (5-10 ppm) showed no toxic effects in rodents. Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) with octamethylcyclotetrasiloxane (D4). Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was a statistically significant reduction in mean litter size and in implantation sites. No D4



**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
Acetoxy Sanitary Sealant**

related clinical signs were observed in the pups and no exposure related pathological findings were found. Interim results from a two generation reproductive study in rats exposed to 500 and 700 ppm D4 (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) resulted in a statistically significant decrease in live mean litter size as well as extended periods of off-spring delivery (dystocia). These results were not observed at the 70 and 300 ppm dosing levels. Preliminary results from an ongoing 24-month combined chronic/oncogenicity study in rats exposed to 10, 30, 150, or 700 ppm D4 showed test-article related effects in the kidney (male and female) and uterus of rats exposed for 12 to 24 months. These effects include increased kidney weight and severity of chronic nephropathy, increased uterine weight, increased incidence of endometrial cell hyperplasia, and an increased incidence of endometrial adenomas. All of these effects are limited to the 700 ppm exposure group. The relevance of these data to humans is unclear. Further studies are ongoing. In developmental toxicity studies, rats and rabbits were exposed to octamethylcyclotetrasiloxane at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study.

SENSITIZATION

no data available

SKIN IRRITATION

no data available

EYE IRRITATION

no data available

MUTAGENICITY

Unknown

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGY

no data available

CHEMICAL FATE

no data available

DISTRIBUTION

no data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Not Regulated if Section is Blank

**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
Acetoxy Sanitary Sealant**

15. REGULATORY INFORMATION

Inventories

TSCA list	y (positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)
Canada NDSL Inventory	n (Negative listing)
EU list of existing chemical substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Canada DSL Inventory	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)

For inventories that are marked as quantity restricted or special cases, please contact GE.

US Regulatory Information

CERCLA

PRODUCT COMPOSITION

Chemical

CERCLA Reportable Quantity

CLEAN AIR ACT

CLEAN WATER ACT

SARA SECTION 302

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS

Other

SCHDLE B/HTSUS:

3214.10.00.10 Mastic based on rubber



**SCS1702 12R-Crtrg (0.730 Lbs-0.331 Kg)
Acetoxy Sanitary Sealant**

ECCN: EAR99

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

OTHER

C = ceiling limit NEGL = negligible EST = estimated NF = none found NA = not applicable
UNKN = unknown NE = none established REC = recommended ND = none determined
V = recommended by vendor SKN = skin TS = trade secret R = recommended
MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million
ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2)., These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.